



TS-253E-8G

| | |
|--|---|
| CPU | Intel® Celeron® J6412 4-core/4-thread processor, burst up to 2.6 GHz |
| CPU Architecture | 64-bit x86 |
| Graphic Processors | Intel® UHD Graphics |
| Floating Point Unit | Yes |
| Encryption Engine | Yes (AES-NI) |
| Hardware-accelerated Transcoding | Yes |
| System Memory | 8 GB SODIMM DDR4 (1 x 8 GB) Since 2024/01 |
| Maximum Memory | 16 GB (2 x 8GB) |
| Memory Slot | 2 x SODIMM DDR4 |
| Flash Memory | 4GB (Dual boot OS protection) |
| Drive Bay | 2 x 3.5-inch SATA 6Gb/s The system is shipped without HDD. For the HDD compatibility list, please visit https://www.qnap.com/compatibility/ |
| Drive Compatibility | 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| Hot-swappable | Yes (Not supported M.2 SSD) |
| M.2 Slot | 2 x M.2 2280 PCIe Gen 3 x2 Compatible with NVMe SSD PCIe Gen 3 and above. Please refer to https://www.qnap.com/compatibility/ for compatibility. |
| SSD Cache Acceleration Support | Yes |
| 2.5 Gigabit Ethernet Port (2.5G/1G/100M) | 2 (2.5G/1G/100M/10M) |
| Wake on LAN (WOL) | Yes |

| | |
|---|---|
| Jumbo Frame | Yes |
| USB 2.0 port | 2 |
| USB 3.2 Gen 2 (10Gbps) Port | 2 x Type-A |
| HDMI™ Output | 2 x HDMI™ 1.4b (up to 3840 x 2160 @ 30Hz) |
| Form Factor | Tower |
| LED Indicators | Power/Status, LAN, USB, HDD1-2 |
| Buttons | Power, Reset, USB Auto Copy |
| Dimensions (HxWxD) | 165 × 102 × 220.6 mm Dimensions do not include foot pad (foot pad may be up to 30mm / 1.18 inches high depending on model) |
| Weight (Net) | 2.57 kg |
| Weight (Gross) | 2.57 kg |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 60W/65W adapter, 100-240V |
| Power Consumption: Disk Standby Mode | 20.943 |
| Power Consumption: Operating Mode, Typical | 24.238 W |
| Fan | 1 x 70mm, 12VDC |
| System Warning | Buzzer |
| Kensington Security Slot | Yes |
| Standard Warranty | 3 |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 1500 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.