

DHI-LM25-B200BS

Dahua 25-inch FHD Monitor



- 178° (H) / 178° (V) extra-wide viewing angle for overall viewing performance.
- VA panel for wide viewing angles with 3-sided micro edge frame design.
- Anti-blue light design and eye-protective.
- 5 ms fast response time with no image blurring or ghosting.

Technical Specification

Display

Model	DHI-LM25-B200BS
LCD Technology	VA
Backlight	ELED
Screen Size	24.5 inch
Aspect Ratio	16:9
Resolution	1920 (H) × 1080 (V)
Refresh Rate	100 Hz
Display Color	8 bit
Color Gamut	72% NTSC
Brightness	250 cd/m ² (max)
Contrast Ratio	3000: 1
Viewing Angle	178° (H) / 178° (V)
Display Mode	Horizontal
Response Time	OD 5 ms
Lifespan	30,000 hrs
Surface Treatment	Haze 25%

Device Ports

Input Port	1 × HDMI 1.4 (1080P@100 Hz), 1 × VGA (1080P@75 Hz)
Speaker	1 W × 2

Power & Environmental Conditions

Power Supply	12 VDC, 2.5 A
Power Type	power adapter
Power Consumption	21 W (basic), 24 W (typ.), 24 W (max)

Standby Power Consumption	≤0.5 W
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Operating Humidity	10%–90% (RH)
Storage Temperature	–20 °C to +60 °C (–4 °F to +140 °F)
Storage Humidity	5%–90% (RH)

General

Inclined Angle	–5° ± 2° / 15° ± 2°
Product Dimensions	558.1 mm × 328.1mm × 41.3mm (21.97" × 12.92" × 1.63") (W × H × D) without base
Package Size	646 mm × 411 mm × 121 mm (25.44" × 16.18" × 4.77") (W × H × D)
Frame Width	U/L/R/D: 1.7 mm/1.7 mm/1.7 mm/16.0 mm
Net Weight	3.2 kg (7.05 lb)
Gross Weight	4.6 kg (10.14 lb)
Accessory	Power adapter, base, HDMI cable, user's manual (QR code), QSG, legal and regulatory information, etc.
Optional Accessory	Wall mount
Wall Mount VESA	75 mm × 75 mm (2.95" × 2.95")

Certification

Certifications	CE EMC, CE LVD, CE ERP
----------------	------------------------

Ordering Information

Type	Model	Description
LED Monitor	DHI-LM25-B200BS	Dahua 25-inch FHD Monitor

DHI-LM25-B200BS

Dimensions (mm[inch])

