

GRAPHICS CARDS GEForce RTX[™] 5070 Ti 16G VENTUS 3X OC









SPECIFICATIONS

Marketing Name	GeForce RTX [™] 5070 Ti 16G VENTUS 3X OC
Model Name	G507T-16V3C
Graphics Processing Unit	NVIDIA [®] GeForce RTX [™] 5070 Ti
Interface	PCI Express [®] Gen 5
Core Clocks	Extreme Performance: 2497 MHz (MSI Center) Boost: 2482 MHz
CUDA [®] CORES	8960 Units
Memory Speed	28 Gbps
Memory	16GB GDDR7
Memory Bus	256-bit
Output	DisplayPort x 3 (v2.1b) HDMI [™] x 1 (As specified in HDMI [™] 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption	300W
Power connectors	16-pin x1
Recommended PSU	750W
Card Dimension (mm)	303 x 121 x 49 mm
Weight (Card / Package)	1073 g / 1566 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC [®] technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.

TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickelplated copper baseplate and transferred.

Core Pipes



Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.

Metal Backplate



A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.

🔊 Zero Frozr



The fans completely stop when temperatures are relatively low, eliminating all noise.

DrMOS



DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.

Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

Afterburner



Take full control with the most recognized and widely used graphics card overclocking software in the world.